## Dati tecnici catena calibrata :

	QUTY PCS	TOTAL LENGTH	SIZE				TENSILE TEST				CHEMCAL COMPOSTION								
DESCRIPTION OF GOODS			D mm	L mm	B mm	b mm	BREAKING LOAD (KN)	PROOF LOAD (KN)	WORKING LOAD (KG)	ELONGATION %	C	Si	Mn	р	S	Cr	Ni	MO	
DIN766 SHOR	DIN766 SHORT LINK CHAIN HOT DIPPED GALV. 100M / PC															· ·			
6.0MM	88	8800M	6.0	18.5	19.8		17.0	10.0	400		0.16			0.02	0.02			<u></u>	
8.0MM	37	3700M	8.0	24.2	27.5		34.0	· 20.0	800		0.16	1.50		0.02	0.02				
DIN766 SHOR	DIN766 SHORT LINK CHAIN STAINLESS STEEL AISI316 100M / PC																		
8.0MM	2	200M	8.0	24.2	-		34.0	16.0	800	,	0.06	0.59	1.64	0.01	0.01	16.2	10.2	2.2	
DIN766 SHOR	DIN766 SHORT LINK CHAIN HOT DIPPED GALV. 100M / PC															-			
10.0MM	18	1800M	10.0	30.3	34.5		52.5	32.0	1250		0.16			0.02	0.02		- "		
12:0MM	2	200M	12.0	36.4	39.6		75.0	45.2	1800		0.16	1		0.02	0.02		<u> </u>		
. Inc. A. Sain							-	,						-		AAAAA MARKATAN	version and the second		
	TEST RESULT: QUALIFIED							INSPECTOR:MR. PAN				INSPECTION DATE: March 16, 2010							